

TR01WSUA0-UN / TR01WSUA0-UN-W

## Travel Adapter

Smart Travel Adapter with USB Port



TR01WSUA0-UN-W



TR01WSUB0-UN

CyberPower Travel Adapter eliminates the need to carry multiple adapter plugs. Its design features a universal outlet that accepts nearly any appliance's plug configuration.

The USB power outlet is perfect use with most of standard USB powered devices. Now you can easy travel with your cell phones, PDAs, video game consoles, and digital cameras with easy charging possibility!

### APPLICATIONS

- Computers & Laptops
- Small Electronics
- Devices with standard USB plug
- Smart Phone, Tablet and other mobile devices

### SERIES FEATURES

- Compact size
- Power outlets applicable in USA/Europe/Australia/UK
- USB Charging Port(s)\*
- Worldwide compatibility covers more than 150 countries \*\*

\* TR01WSUA0-UN-W = 5V/1A

TR01WSUB0-UN = 5V/2.4A

\*\* most parts of North America and South America, Australia, Europe, Africa, Asia, Great Britain, Ireland, Singapore, China, Japan, the Middle East, the Caribbean, New Zealand, Fiji and more. It's worldwide compatibility covers more than 150 countries).



## TECHNICAL SPECIFICATION

Model Name	TR01WSUA0-UN-W	TR01WSUB0-UN
<b>Input</b>		
Voltage	100~240V	100~240V
Rating	6A	6A
Plug Type	UK/EU/US/AU	UK/EU/US/AU
<b>Output</b>		
Outlets - Total	1	1
Outlet Type	Universal	Universal
USB Charging Ports	5V/1A	5V/2.4A
# of USB Ports	1	2
<b>Indicators</b>		
Indicators	On/Off	On/Off
<b>Physical</b>		
Form Factor	adapter	adapter
Enclosure Construction	PC	PC
Color	White	Black
Safety Covers	Yes	Yes
<b>Physical Size</b>		
Dimensions (WxHxD) (mm.)	48 x 55.5 x 66.5	48 x 55.5 x 66.5
<b>Environmental</b>		
Operating Temperature	32 °F to 95 °F / 0 °C to 35 °C	32 °F to 95 °F / 0 °C to 35 °C
Operating Humidity	0% - 95% non-condensing	0% - 95% non-condensing
Storage Temperature	5 °F to 113°F / -15°C to 45 °C	5 °F to 113°F / -15°C to 45 °C
Maximum Operating Elevation	10,000 feet / 3,000 meters	10,000 feet / 3,000 meters
Maximum Storage Elevation	50,000 feet / 15,000 meters	50,000 feet / 15,000 meters
<b>Certifications</b>		
RoHS	RoHS Compliant	RoHS Compliant
<b>Warranty</b>		
Product Warranty	1 year	1 year

